



RES SMT 360™ Multi-GNSS Timing Module

KEY FEATURES

- Multi-Constellation
- Simultaneous GPS / GLONASS or GPS / Beidou tracking
- Ideal for populated urban and indoor environments with limited sky-view
- PPS and PP2S outputs, synchronized to GNSS / UTC within 15ns (1 sigma)
- Extended temperature range (-40°C / +85°C)

Miniature Multi-GNSS Timing Module with Super-Sized Features

Ideal for Low Signal Environment
Trimble® designed the RES SMT 360™ Timing Module to work in the most demanding weak signal environments, including femtocells and in-building systems.

With its robust performance in low signal environments, users can save on expensive cabling and externally mounted antennas. In addition, the RES SMT 360™ timing module accepts aiding data for environments requiring the highest levels of enhanced sensitivity.

PPS and Frequency Outputs

The RES SMT 360™ timing module outputs a precise 1 pulse-per-second (1PPS) and an even second pulse to maximize your network performance and synchronize systems at a global level.

Custom frequencies are also available for volume sale.



Standard Timing Features

The RES SMT 360™ timing module includes many of Trimble's standard timing features, including Time-Receiver Autonomous Integrity Monitoring (T-RAIM) algorithm, automatic self-survey, and GNSS disciplining of the oscillator to provide an accurate frequency reference

Carrier Board and Starter Kit Options

The RES SMT 360™ timing module can be loaded directly onto the customer's application board.

The Starter Kit provides everything you need to evaluate the RES SMT 360™ timing module, including the RES SMT 360™ on a carrier board, AC/DC power converter, antenna and USB interface cable.

RES SMT 360™ Multi-GNSS TIMING MODULE

GENERAL SPECIFICATIONS

Receiving Signal.....GPS, GLONASS, Galileo, Beidou
 Supports GNSS incl.SBAS, QZSS
 Positioning System.....SPS, Timing
 1 PPS Timing Accuracy15 ns (1 sigma)
 Update Rate.....1 Hz
 Typical Min Acq Sensitivity.....-148dBm cold start
 Typical Min Tracking Sensitivity -160dBm
 Time to First Fix.....<46s (50%), <50s (90%) cold start
 Typical Time to Re-acquisition..... <2s (90%)

INTERFACE CHARACTERISTICS

Connections.28 surface-mount edge castellations
 Serial Port.....2 serial port
 PPS / Even Second.....CMOS-compatible
 LVTTTL-level pulse, once per second
 Protocols.....TSIP, NMEA 0183

PINOUT ASSIGNMENTS

| ICM-SMT 360 PINOUTS | | | |
|---------------------|---------------|----------|----|
| 1 | GND | GND | 28 |
| 2 | GND | VCC | 27 |
| 3 | RFIN | GND | 26 |
| 4 | GND | EXTRESET | 25 |
| 5 | OPEN | GND | 24 |
| 6 | SHORT | SYSCLK | 23 |
| 7 | NC | TXD2 | 22 |
| 8 | NC | RXD2 | 21 |
| 9 | NC | GND | 20 |
| 10 | NC | 1PPS | 19 |
| 11 | PPS_IN | GND | 18 |
| 12 | HW_ALARM | TXD | 17 |
| 13 | AUX1 (BOOT_0) | RXD | 16 |
| 14 | GND | GND | 15 |

PHYSICAL CHARACTERISTICS

Enclosure.....Metal Shield
 Dimensions19 mm W x 19 mm L x 2.54 mm H
 (0.75" W x 0.75" L x 0.1" H)
 Weight.....1.8 grams (0.06 ounce) including shield

ELECTRICAL CHARACTERISTICS

Supply Voltage Range.....3.3VDC to ±5%
 Power Consumption.....0.5W max.

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature.....-40°C to +85°C
 Operating Humidity.....5%-95% RH non-condensing (+60°C)
 Storage Temperature.....-50°C to +105°C

GENERAL INFORMATION & ACCESSORIES

Module.....available in 20 piece trays for evaluation
 Production quantities on tape on reel (500 pieces)

Reference Board.....GNSS module mounted on a carrier board with I/O and RF connectors, including RF circuitry with the antenna open detection, as well as antenna short detection and protection.

Starter KitIncludes Reference Board mounted on interface motherboard in a durable metal enclosure, AC/DC power converter, Bullet 360 antenna, USB interface cable, TSIP and NMEA protocols

Antenna..... Bullet 360

Visit www.trimble.com/timing for part numbers and information about where to buy.

Parts of the product are patent protected.

Trimble has relied on representations made by its suppliers in certifying this product as RoHS-II compliant.

Specifications subject to change without notice.

Trimble Navigation Limited is not responsible for the operation or failure of operation of GPS satellites or the availability of GPS satellite signal.

NORTH AMERICA

Trimble Navigation Limited
 Corporate Headquarters
 935 Stewart Drive
 Sunnyvale, CA 94085
 Phone: +1 408.481 7741
 timing@trimble.com

EUROPE

Trimble Navigation Europe
 Phone: +4670-544-1020

KOREA

Trimble Export Ltd. Korea
 Phone: +82-2-555-5361

CHINA

Trimble Navigation Ltd. China
 Phone: +86-10-8857-7575



www.trimble.com